



Kleuren	Coloris	Farben	Colours
2812 Sand			
2814 Brown			
2815 Cognac			
2816 Grey/Beige			
2817 Greige			
2818 Choclat			
2819 Tobacco			

OPTIK filc

Fabricagemethode	Méthode de fabrication	Herstellungsverfahren	Manufacturing process
Getuft 5/32" lussen pool	Tuftée 5/32" bouclé	Getuftet 5/32" Schlinge	Tufting 5/32" loop-pile
Pool Samenstelling 100% polypropylene	Composition du velours 100% polypropylene	Polmaterial 100% Polypropylene	Pile content 100% polypropylene
Tuftdoek Geweven PP	Support Tissé PP	Trägermaterial PP Gewebe	Primary backing Woven PP
Rug A.B. + Vlies	Dossier A.B. + Feutre	Rückenausrüstung A.B. + Vlies	Secondary backing A.B. + Felt
Poolgewicht ca. 850 gr/m2.	Poids du velours ca. 850 gr/m2.	Polgewicht ca. 850 gr/m2.	Pile weight ca. 850 gr/m2.
Totaalgewicht A.B. : ca. 2100 gr/m2.. Vlies: ca. 2200 gr/m2.	Poids total A.B. : ca. 2100 gr/m2. Feutre: ca. 2200 gr/m2.	Gesamtgewicht A.B. : ca. 2100 gr/m2. Vlies: ca. 2200 gr/m2.	Total weight A.B. : ca. 2100 gr/m2. Felt : ca. 2200 gr/m2.
Poolhoogte ca. 6 mm.	Hauteur du poil ca. 6 mm.	Polhöhe ca. 6 mm.	Pile height ca. 6 mm.
Totale hoogte A.B. : ca. 8 mm. Vlies: ca. 10 mm.	Hauteur total A.B. : ca. 8 mm. Feutre : ca. 10 mm.	Gesamthöhe A.B. ca. 8 mm. Vlies: ca. 10 mm.	Total height A.B. : ca. 8 mm. Felt : ca. 10 mm.
Aantal noppen ca. 101.400 m2.	Nombre de points ca. 101.400 m2.	Noppenzahl ca. 101.400 m2.	Number of knots ca. 101.400 m2.
Breedte 400 + 500 cm.	Largeur 400 + 500 cm.	Breite 400 + 500 cm.	Width 400 + 500 cm.
Aantal kleuren 7	Nombre de coloris 7	Farbenzahl 7	Number of colours 7
Lichtechtheid ISO 105 B02: 5 tot 8	Résistance à la lumière ISO 105 B02: 5 à 8	Lichtechtheit ISO 105 B02: 5 bis 8	Light fastness ISO 105 B02: 5 to 8
Waterechtheid EN 1307, annex F: 5	Résistance à l'eau EN 1307, annex F: 5	Wasserechtheit EN 1307, annex F: 5	Water resistance EN 1307, annex F: 5
Vlamwerend BS4790 A.B. : Low Radius of Ignition Vlies : High Radius of Ignition	Tenue au feu BS4790 A.B. : Low Radius of Ignition Feutre: High Radius of Ignition	Brennverhalten BS4790 A.B. : Low Radius of Ignition Vlies : High Radius of Ignition	Combustibility BS4790 A.B. : Low Radius of Ignition Felt : High Radius of Ignition
Bijzonderheden Felt DOP Nr. 1058-115034 Felt GUT 20DF10F6	Caractéristiques -	Besonderheiten -	Characteristics -

