

ROCKET



Luxury Carpet Tiles

CONSTRUCTION Tufted 1/10" Loop	STRUCTURE Tufté 1/10" Bouclé	STRUKTUR Getuftet 1/10" Schlinge	STRUCTUUR Getuft 1/10" Luspool
PILE MATERIAL 100% PA6 Solution Dyed Nylon	COUCHE D'USURE 100% PA6 Solution Dyed Nylon	POLMATERIAAL 100% PA6 Solution Dyed Nylon	POOLMATERIAAL 100% PA6 Solution Dyed Nylon
SECONDARY BACKING Back2Back : Modified bitumen	DOSSIER Back2Back : Modified bitumen	RÜCKENAUSSTATTUNG Back2Back : Modified bitumen	RUG Back2Back : Modified bitumen
TOTAL WEIGHT Ca. 4.250 g/m ²	POIDS TOTALE Ca. 4.250 g/m ²	GESAMTGEWICHT Ca. 4.250 g/m ²	TOTAAL GEWICHT Ca. 4.250 g/m ²
PILE WEIGHT Ca. 480 g/m ²	POIDS DU VELOURS Ca. 480 g/m ²	POLEINSATZGEWICHT Ca. 480 g/m ²	POOLGEWICHT Ca. 480 g/m ²
PILE ABOVE BACKING Ca. 273 g/m ²	POIDS DE VELOURS UTILE Ca. 273 g/m ²	POLNUTZSCHICHTGEWICHT Ca. 273 g/m ²	NUTTIG POOLGEWICHT Ca. 273 g/m ²
TOTAL HEIGHT Ca. 6,0 mm	EPAISSEUR TOTALE Ca. 6,0 mm	GESAMTHÖHE Ca. 6,0 mm	TOTAAL HOOGTE Ca. 6,0 mm
PILE HEIGHT Ca. 2,5 mm	HAUTEUR DU VELOURS Ca. 2,5 mm	POLDICKE Ca. 2,5 mm	POOLHOOGTE Ca. 2,5 mm
PILE DENSITY Ca. 0,110 g/cm ³	DENSITÉ DU VELOURS Ca. 0,110 g/cm ³	POLROHDICHTE Ca. 0,110 g/cm ³	POOLDICHTHEID Ca. 0,110 g/cm ³
TUFT DENSITY Ca. 176.000/m ²	NOMBRE DE TOUFFES Ca. 176.000/m ²	NOPPENZAHL Ca. 176.000/m ²	AANTAL PUNTEN Ca. 176.000/m ²
CLASSIFICATION EN 1307 33 - LC1	CLASSEMENT EN 1307 33 - LC1	KLASSIFIKATION EN 1307 33 - LC1	CLASSIFICATIE EN 1307 33 - LC1
CASTOR CHAIR SUITABILITY EN 985 A : continuous use	EMPLOI CHAISE À ROULETTES EN 985 A : continuous use	STUHLROLLENEIGNUNG EN 985 A : continuous use	ROLSTOELGESCHIKTHEID EN 985 A : continuous use
FIRE RESISTANT B _{fl} -s1 (EN 13501-1)	COMPORTEMENT AU FEU B _{fl} -s1 (EN 13501-1)	BRENNVERHALTEN B _{fl} -s1 (EN 13501-1)	BRANDGEDRAG B _{fl} -s1 (EN 13501-1)
FASTNESS TO LIGHT ISO 105-B02 ≥ 7	SOLIDITÉ À LA LUMIÈRE ISO 105-B02 ≥ 7	LICHTECHTHEIT ISO 105-B02 ≥ 7	LICHTECHTHEID ISO 105-B02 ≥ 7
RUBBING FASTNESS ISO 105-X12 ≥ 4	SOLIDITÉ AU FROTTEMENT ISO 105-X12 ≥ 4	REIBECHTHEIT ISO 105-X12 ≥ 4	WRIJFECHTHEID ISO 105-X12 ≥ 4
COLOUR FASTNESS TO WATER EN ISO 105-E01 ≥ 4	SOLIDITÉ À LA LUMIÈRE EN ISO 105-E01 ≥ 4	WASSERECHEIT EN ISO 105-E01 ≥ 4	WATERECHEIT EN ISO 105-E01 ≥ 4
THERMAL RESISTANCE ISO 8302 - 0,067 m ² K/W	RÉSISTANCE THERMIQUE ISO 8302 - 0,067 m ² K/W	WÄRMEDURCHLASSWIDERSTAND ISO 8302 - 0,067 m ² K/W	WARMTEDOORLAATWEERSTAND ISO 8302 - 0,067 m ² K/W
IMPACT NOISE RATING ISO 10140 ΔL _w : 24dB	ISOLATION PHONIQUE ISO 10140 ΔL _w : 24dB	TRITTSCHALLVERBESSERUNGSMASS ISO 10140 ΔL _w : 24dB	GELUIDSISOLATIE ISO 10140 ΔL _w : 24dB
SOUND ABSORPTION ISO 354 α _w : 0,15	ABSORPTION PHONIQUE ISO 354 α _w : 0,15	SCHALLABSORPTIONSGRAD ISO 354 α _w : 0,15	GELUIDSABSORPTIE ISO 354 α _w : 0,15
PERMANENT ANTISTATIC ISO 6356 ≤ 2 kV	ANTISTATIQUE PERMANENT ISO 6356 ≤ 2 kV	PERMANENT ANTISTATISCH ISO 6356 ≤ 2 kV	PERMANENT ANTISTATISCH ISO 6356 ≤ 2 kV
TRANSVERSAL RESISTANCE ISO/DIS 10965 ≤ 10 ⁹ Ohm	RÉSISTANCE TRANSVERSALE ISO/DIS 10965 ≤ 10 ⁹ Ohm	DURCHGANGSWIDERSTAND ISO/DIS 10965 ≤ 10 ⁹ Ohm	DOORGANGSWEERSTAND ISO/DIS 10965 ≤ 10 ⁹ Ohm
SIZE 50 x 50 cm	DIMENSIONS 50 x 50 cm	ABMESSUNG 50 x 50 cm	AFMETINGEN 50 x 50 cm
PACKAGING Box: 5 m ² - Pallet: 20 boxes	EMBALLAGE Box: 5 m ² - Pallet: 20 boxes	VERPACKUNG Box: 5 m ² - Pallet: 20 boxes	VERPAKKING Box: 5 m ² - Pallet: 20 boxes
DIMENSIONAL STABILITY EN 986 max. 0,2%	STABILITÉ DIMENSIONNELLE EN 986 max. 0,2%	DIMENSIONSTABILITÄT EN 986 max. 0,2%	DIMENSIONELE STABILITEIT EN 986 max. 0,2%

EN 14041

17
NB: 0493
DOP: 0493-CPD-0022

modulyss®
Zevensterrestraat 21
9240 Zele, Belgium
www.modulyss.com

EN 1307
Textile Floor Covering

B_{fl}-s1
DL
PCP
NA
HCHO
DS

F512/02

GREEN LABEL
+PLUS®

Indoor Air Quality
Adhesive Testing Program
carpet-rug.org

M01/17

EMISSIONS DANS L'AIR INTERIEUR

A+

DA05AB07

Order conditions : min. 1000 m²/collection, full pallets/colour, no one batch guarantee



MAINTENANCE: Spillage should be taken up promptly and surface stains removed by an appropriate method as soon as possible. In heavy traffic areas the carpet should be cleaned daily with a vacuum cleaner. Periodic maintenance should be carried out by professional cleaning staff using appropriate extraction systems. COLOUR MATCHING: As with all textile products there will be a variance in shade from batch to batch. Any samples supplied are as close a representation to the actual carpet as the production process will allow. An exact colour match between different dye batches cannot be guaranteed.


ROCKET




Luxury Carpet Tiles




▲ 504



▲ 553




▲ 914



▲ 961



▲ 994



▲ 990