

TRENTO



Guarantee

Garantie

Garantie


Garantie



	Product information Produkt informatie	Produkt Daten Information produit		
	Total thickness Totale dikte	Gesamtstärke Epaisseur totale	EN 428	2,80 mm
	Wearlayer Slijtlaag	Nutzschicht Couche d'usure	EN 429	0,25 mm
	Width Breedte	Breite Largeur	EN 426	2m 3m 4m
	Standard length Standard rollengte	Standard Rollenlänge Longueur standard	EN 426	30 m
	Total roll weight Totaal rolgewicht	Total Rollengewicht Poids total des rouleaux		100kg 150kg 200 kg
	Classification Classificatie	Klassifizierung Classification	EN 685	23
				31

	Technical information Technische informatie	Technische Daten Information technique		
	Light stability Lichtechtheid	Lichtechtheit Résistance à la lumière	ISO 105-B02	≥ 6
	Dimensional stability Dimensionele stabiliteit	Dimensionsstabilität Stabilité dimensionnelle	EN 434	≤ 0,40%
	Underfloor heating Vloerverwarming	Fussbodenheizung Chauffage par le sol	EN 12667	Suitable Geschikt Geeignet Convenable

TRENTO

	Residual indentation Restindrukking	Eindruckverhalten Poinçonnement	EN 433	≤ 0,35 mm
	Reaction to fire Brandklasse	Brandverhalten Indice d'incendie	EN 13501-1	B _{fl} S1
	Slipresistance Slipweerstand	Rutschhemmung Glissance	EN 13893	DS



B.I.G. Floorcoverings
Rijksweg 442
8710 - Wielsbeke

06

EN 14041:2004

Expanded (cushioned) polyvinyl
chloride floor coverings (EN653)

Reaction to fire : Class Bfl/s1

Slipperiness : DS

Formaldehyde : E1

EN 653